

ASTROBIO™ MT

Bio-Solvents Blend, metal surfaces degreaser and cleaner Technical Data Sheet

Product name: ASTROBIO™ MT
Manufacturer: Liberty Chemicals s.r.l. (Italy)
Contact: info@astrobiosolvent.com

Area of Use:

ASTROBIO™ MT is a high performance, plant based bio-solvent suitable for cleaning and degreasing operations in many industrial settings. **Outstanding performances for cleaning and degreasing metal surfaces.** It's a slow evaporating solvent used to manufacture eco-friendly professional and household metal cleaners, inks, graffiti removers and paints strippers. It's used for cleaning and maintenance procedure of industrial machinery (particularly in printing industry, e.g. for rollers and printing cylinders). Its hydrophilic nature makes it an ideal ingredient for water based cleaners and detergents. **ASTROBIO™ MT can efficiently dissolve greases, fats, oils, lubricants and, among others, coatings, paints and inks** based on acrylics, epoxies, nitrocellulose and vinylics resins.

Technical Benefits:

- 20% -30% more efficient than conventional solvents.
- Dries completely and leaves no residue.
- Easy and inexpensive to distill or recycle.
- **Exceptional performance as an ingredient for cleaning formulations.**
- Strong solvency power towards several resins, fats, greases and oils.
- **Reduced solvent usage: stays on the job longer.**
- Versatile in a wide range of applications.

Available Packaging:

Drums	IBC	Bulk
218Kg	1090Kg	≥ 10MT
net weight	net weight	net weight



Key Features:

Bio-based solvent according to EN 16575

Flashpoint	81° C	EN 3679
RER (BuOAc=1)	0,002	Calculated
Vap. pressure (20°C)	0,19 kPa	Calculated
Boiling Range	151° - 240°C	-

Solvency power:

HSP's	δd	δp	δh	δt	Calculated
	18,00	11,00	8,00	23,00	

Environmental Benefits:

- Readily biodegradable raw materials.
- Slow Climate change: carbon neutral balance.
- Sustainable chemistry: renewable raw materials.
- No ozone depleting chemicals.
- No environmental hazardous ingredients.
- No hazardous air pollutants.

Health Benefits:

- Chlorine, Halogens, Ketons, Aromatic and paraffins free.
- **Non flammable, light labelling.**
- Faint and pleasant smell.

LIBERTY CHEMICALS s.r.l.

Guaranteed Specifications

Properties	Standard	ASTROBIO™ MT	Units
Appearance	Visual	Clear colourless liquid	-
Colour	ASTRO001 ¹	30	Pt-Co (APHA), Max
Specific gravity (20°C)	ASTRO002 ¹	1,06 – 1,12	g/mL
Moisture	ASTRO003 ¹	0,2	% in weight, max

Technical Performances and properties

Properties	Standard	ASTROBIO™ MT				Units
Chemical composition	-	Blend of organic acids esters ²				-
Solvency power: HSP's	Calculated	δd	δp	δh	δt	Mpa ^{1/2}
		18,00	11,00	8,00	23,00	
Boiling range	-	151 - 240				°C
Flashpoint	EN 3679	81				°C
Evaporation rate	Calculated	0,002				RER (BuOAc=1)
Vapor pressure (20° C)	Calculated	0,19				kPa
Dynamic Viscosity (25° C)	ASTRO004 ¹	≈ 1,81				mPa.s

Environmental characteristics and Biodegradability

Properties	Standard/Reference	ASTROBIO™ MT	Units
Ready Biodegradability ³	OECD 301 series	> 85	% w/w in 10 days window
Ultimate biodegradability ⁴	-	100	% w/w at 67 days
Water hazard	WGK Germany	1	Class
VOC content	Directive 2010/75/UE and Swiss Regulation (814.018)	51,3	% w/w
	Directive 2004/42/CE	100	% w/w

This product has to be subjected from any industrial or professional user to careful tests, in order to evaluate his effectiveness for expected applications. Our company waives any responsibility in case of any improper usage of this product.

Manufactured in Italy (European Union).
ASTROBIO™ is a trade mark of Liberty Chemicals s.r.l.
 (Italy)

Issued by: ASTROBIO™ division | Liberty Chemicals s.r.l. (Italy).

LIBERTY CHEMICALS s.r.l.

Footnotes:

1. Analysis conducted according to an internal standard protocol.
2. All ingredient are REACH registered.
3. Product has not been tested itself to access ready biodegradability, but all raw materials used during manufacture are classified as readily biodegradable according to one or several of the following OECD guidelines: OECD 301 A, B, C, D, E, F.
4. Product has not been tested itself to access ultimate biodegradability, but all raw materials used during manufacture are completely (100%) biodegradable in 67 days or less.